# SAFETY DATA FINGERTENS PTY LTD ww

# SHEET

www.fingertens.com.au



Date 10/01/2019

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

#### **Product Identifier**

## **Grill Power**

## Recommended use of the chemical and restrictions on use

Oven and grill cleaner.

## Details of the supplier of the safety data sheet:

FINGERTENS Pty Ltd

Suite 1A / Level 2 802 Pacific Highway

Gordon NSW 2072

EMail admin@fingertens.com.au

Web Site: www.fingertens.com.au

Telephone: 1300 855 273 Facsimile: 1300 855 274

## **Emergency Telephone Number:**

131126 Poisons Information Centre

## 2. HAZARDS IDENTIFICATION

## Classification of the substance or mixture

Classified as hazardous according to Safe Work Australia criteria.

Skin corrosion - category 1A

#### Label elements

#### Hazard pictogram



## **Signal Word**

Danger

#### **Hazard Statements**

H314 Causes severe skin burns and eye damage

#### **Precautionary Statements**

#### General

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

SDS Grill Power 10/01/2019 Page 1 of 9

#### Prevention

P260 Do not breathe vapours.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ clothing and eye/ face protection

#### Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P363 Wash contaminated clothing before reuse.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P310 Immediately call a POISON CENTER or doctor.

P321 Specific treatment (see supplemental first aid instructions on this label).

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### Storage

P405 Store locked up

#### Disposal

P510 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Other hazards

Poisons Schedule (SUSMP) S6 POISON

## 3. COMPOSITION INFORMATION

INGREDIENT	PROPORTION	CAS NUMBER
Sodium hydroxide; caustic soda	10 < 20 %	1310-73-2
Potassium hydroxide; caustic potash	< 10%	1310-58-3
(2-Methoxymethylethoxy) propanol; Dipropylene glycol (mono) methyl ether	< 5%	34590-94-8
2-aminoethanol; ethanolamine	< 5%	141-43-5

## 4. FIRST AID MEASURES

#### Description of first aid measures

For advice, contact a Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

#### Inhalation

If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

#### Skin contact

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

#### **Eve contact**

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

#### Ingestion

If swallowed, do NOT induce vomiting.

SDS Grill Power 10/01/2019 Page 2 of 9

#### Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

#### **Extinguishing media**

Not combustible. If material is involved in a fire use: fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

## Special hazards arising from the substance or mixture

Not combustible. Decomposes on heating emitting toxic fumes.

#### Advice for firefighters

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition. Keep containers cool with water spray.

#### **Hazchem Code**

2R

#### 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

Wear protective equipment to prevent skin and eye contact and breathing in vapours. Shut off all possible sources of ignition. Work

up wind or increase ventilation. Clear area of all unprotected personnel. Contact local emergency services where appropriate.

#### **Environmental precautions**

Avoid contaminating waterways. If contamination of sewers or waterways has occurred advise local emergency services.

#### Methods and material for containment and cleaning up

Contain using sand or soil. Prevent run off into drains or waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

#### Reference to other sections

See Section 8 for appropriate personal protective equipment. See Section 13 for waste treatment methods.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

## Conditions for safe storage, including any incompatibilities

This product is a Scheduled Poison (S6) and must be stored, maintained and used in accordance with the relevant regulations. Store in a cool, dry, well ventilated place out of direct sunlight. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep container standing upright. Keep containers closed when not in use.

Check regularly for leaks.

## Specific end uses

See Section 1.

SDS Grill Power 10/01/2019 Page 3 of 9

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **Control parameters**

No exposure standard assigned for this specific material by the Safe Work Australia.

Ingredient	TWA ppm	TWA (mg/m³)	STEL ppm	STEL (mg/m³)
Sodium hydroxide; caustic soda		2 Peak Limitation		
Potassium hydroxide; caustic potash		2 Peak Limitation		
ic potash 2 Peak limitation (2-Methoxymethylethoxy) propanol; Dipropylene glycol (mono) methyl ether	50	308		
2-aminoethanol; ethanolamine	3	7.5	6	15

As published by Safe Work Australia.

Time weighted average exposure standard (TWA) means the average airborne concentration of a substance over an eight-hour working day, for a five-day working week.

Peak limitation means a maximum or peak airborne concentration of a substance determined over the shortest analytically practicable period of time which does not exceed 15 minutes.

Short term exposure limit (STEL) means the average airborne concentration of a substance calculated over a 15 minute period. The STEL should not be exceeded at any time during a normal eight hour working day.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## **Exposure controls**

## Appropriate engineering controls

Ensure ventilation is adequate and that air concentrations of components are controlled below workplace exposure standards. Avoid generating and inhaling mists. If inhalation risk exists use with local exhaust ventilation or while wearing suitable mist respirator. Keep containers closed when not in use.

#### Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

## Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Refer to Australian/New Zealand Standard AS/NZS 1337:1992 for guidance on selection and use of protective eyewear.

#### Skin protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Refer to Australian/New Zealand Standard AS/NZS 2161.1: 2000 for guidance on selection and use of protective gloves. Personal protective equipment for the body, appropriate footwear and any additional skin protection should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Refer to Australian/New Zealand Standard AS/NZS 1715 and AS/NZS 1716 for guidance on selection and use of respiratory devices.

SDS Grill Power 10/01/2019 Page 4 of 9

#### General safety and hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## **Environmental exposure controls**

Not available

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Appearance Light Brown liquid

Odour Bland

Odour threshold Not available 12.0 - 14.0рН Melting point/freezing point Not available Initial boiling point and boiling range Not available Flash point Not available Evaporation rate Not available Flammability (solid, gas) Not available Upper/lower flammability or explosive limits Not available Vapour pressure Not available Vapour density Not available Relative density 1.3 Solubility Soluble in water Partition coefficient: n-octanol/water Not available Not available

Auto-ignition temperature

Decomposition temperature

Viscosity

Not available

Not available

Not available

Not available

Not available

Not applicable

Oxidising properties

Not applicable

#### Other information

No additional information

## 10. STABILITY AND REACTIVITY

#### Reactivity

No hazardous reactions under normal storage and use conditions.

#### Chemical stability

Stable under normal storage and use conditions.

## Possibility of hazardous reactions

No hazardous reactions known under normal storage and use conditions.

#### Conditions to avoid

Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame. Avoid contact with other chemicals.

#### Incompatible materials

Incompatible with acids and oxidizing agents.

## **Hazardous decomposition products**

None known under normal storage and use conditions.

SDS Grill Power 10/01/2019 Page 5 of 9

#### 11. TOXICOLOGICAL INFORMATION

Acute toxicity: No data available for the mixture

Ingredient	Oral Toxicity (LD50)	Dermal Toxicity(LD50)	Inhalation Toxicity(LC50)
Sodium hydroxide; caustic soda	500 mg/kg (rat)	1,350 mg/kg (rabbit)	
Potassium hydroxide; caustic potash	273 mg/kg (rat)		
(2-Methoxymethylethoxy) propanol; Dipropylene glycol (mono) methyl ether	>5,000 mg/kg (rat)	9,510 mg/kg (rat)	
2-aminoethanol; ethanolamine	600-800 mg/kg (rat)	1000 mg/kg (rabbit)	

**Skin corrosion/irritation:** Causes severe skin burns.

Serious eye damage/irritation: Causes severe eye damage.

Respiratory or skin sensitisation: No data available

Germ cell mutagenicity: No data available

Carcinogenicity: No data available

Reproductive toxicity: No data available

Summary of evaluation of the CMR properties: No data available

Specific Target Organ Toxicity (STOT)-single exposure: No data available

Specific Target Organ Toxicity (STOT)-repeated exposure: No data available

Aspiration hazard: No data available

## Information on likely routes of exposure

#### Inhalation:

Breathing in mists may produce respiratory irritation.

#### Skin contact:

Contact with the skin can result in severe irritation. Corrosive to skin. May cause skin burns.

#### Eye contact:

A severe eye irritant. Corrosive to eyes. Contact can cause corneal burns. Contamination of eyes can result in permanent injury.

#### Ingestion:

Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

## Symptoms related to the physical, chemical and toxicological characteristics

May cause redness and tearing of the eyes. May cause burns to eyes. May cause redness or burns to skin. Inhalation may cause coughing.

Delayed and immediate effects as well as chronic effects from short and long term exposure No information available.

## Numerical measures of toxicity

Acute oral toxicity estimate (ATE) > 2000 mg/kg

SDS Grill Power 10/01/2019 Page 6 of 9

#### Interactive effects

No information available.

## 12. ECOLOGICAL INFORMATION

#### **Toxicity**

Avoid contaminating waterways.

#### Persistence and degradability

No data available.

#### Bioaccumulative potential

No data available

## Mobility in soil

No data available

#### Other adverse effects

No data available

#### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Waste must be disposed of in accordance with federal, state and local environmental control regulations. The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers

## 14. TRANSPORT INFORMATION

Classified as a Dangerous Good by the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail.



#### **UN Number**

1719

## **UN Proper shipping name**

CAUSTIC ALKALI LIQUID, N.O.S. (Sodium hydroxide, Potassium hydroxide)

#### Transport hazard class(es):

Class: 8

## **Packing group**

Ш

#### **Environmental hazards:**

No

SDS Grill Power 10/01/2019 Page 7 of 9

## Special precautions for user

None known

## Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

#### Other relevant information:

## **Hazchem Code**

2 R

## 15. REGLATORY INFORMATION

## Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Classification

Globally Harmonised System of Classification and Labelling of Chemicals (GHS) as published by Safework Australia.

## Poison schedule

Classified as a Schedule 6 (S6) Poison using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

## Inventory listing(s)

AICS (Australian Inventory of Chemical Substances): All components are listed on AICS, or are exempt

#### Chemical safety assessment

No chemical safety assessment has been carried out for this substance / mixture by the supplier.

SDS Grill Power 10/01/2019 Page 8 of 9

#### **16. OTHER INFORMATION**

Revision Date Jan 2019

## **Abbreviations and Acronyms**

ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS - Australian Inventory of Chemical Substances

ATE - Acute Toxicity Estimate

CAS - Chemical Abstracts Service Registry Number

GHS - Globally Harmonized System of Classification and Labelling of Chemicals

IBC - Intermediate Bulk Container

IATA - International Air Transport Association

ICAO - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

IMO - International Maritime Organisation

LC50 - Lethal Concentration, 50% / Median Lethal Concentration

MARPOL 73/78 - International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

LD50 - Lethal Dose, 50% / Median Lethal dose

PBT - Persistent, Bioaccumulative and Toxic

STOT-RE - Specific target organ toxicity (repeated exposure)

STOT-SE - Specific target organ toxicity (single exposure)

SUSMP - Standard for the Uniform Scheduling of Medicines & Poisons

**UN - United Nations** 

vPvB - very Persistent and very Bioaccumulative

This MSDS has been prepared by the Technical Manager, Fingertens Pty Ltd.

Reason for issue: Revision

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the manufacturer/supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is available upon request.

SDS Grill Power 10/01/2019 Page 9 of 9